FINDINGS FOR APPROVAL

- 1. The proposed map and its design and improvement, is consistent with the General Plan and applicable Specific Plan in that the lots are intended to be used in compliance with the General Plan and zoning designation. The new parcels can be developed in accordance with the development standards of the zoning of the parcel.
- 2. The design of the subdivision and proposed improvements are not likely to cause environmental damage or substantially and avoidably injure fish, or wildlife, since the project only divides the land into parcels and does not consist of the construction of improvements.
- The design of the subdivision and proposed improvements are not likely to cause serious public health problems due to imposed conditions the fact that the project only divides the land and does not consist of the construction of improvements.
- 4. The design of the proposed map will not conflict with easements acquired by the public at large, for access through, or use of, property within the proposed Map since none presently exist.

GENERAL CONDITIONS OF APPROVAL

The applicant agrees to defend, indemnify and hold harmless the City of La Quinta ("City"), its agents, officers and employees from any claim, action or proceeding to attack, set aside, void, or annul the approval of this Tentative Parcel Map, or any Parcel Map recorded thereunder. The City shall have sole discretion in selecting its defense counsel.

The City shall promptly notify the applicant of any claim, action or proceeding and shall cooperate fully in the defense.

2. This Tentative Parcel Map, and any Parcel Map recorded thereunder, shall comply with the requirements and standards of Government Code §§ 66410 through 66499.58 (the "Subdivision Map Act"), and Chapter 13 of the La Quinta Municipal Code ("LQMC").

The City of La Quinta's Municipal Code can be accessed on the City's Web Site at www://la-quinta.org.

- 3. Prior to the issuance of any grading, construction, or building permit by the City, the applicant shall obtain the necessary clearances and/or permits from the following agencies:
 - Fire Marshal
 - Public Works Department (Grading Permit, Improvement Permit)
 - Community Development Department
 - Riverside Co. Environmental Health Department
 - Desert Sands Unified School District
 - Coachella Valley Water District (CVWD)
 - Imperial Irrigation District (IID)
 - California Water Quality Control Board (CWQCB)
 - SunLine Transit Agency

The applicant is responsible for all requirements of the permits and/or clearances from the above listed agencies. When the requirements include approval of improvement plans, the applicant shall furnish proof of such approvals when submitting those improvements plans for City approval.

- 4. The applicant shall comply with applicable provisions of the City's NPDES stormwater discharge permit, Sections 8.70.010 et seq. (Stormwater Management and Discharge Controls), and 13.24.170 (Clean Air/Clean Water), LQMC; Riverside County Ordinance No. 457; and the State Water Resources Control Board's Order No. 99-08-DWQ.
 - A. For construction activities including clearing, grading or excavation of land that disturbs five (5) acres or more of land, or that disturbs less than five (5) acres of land, but which is a part of a construction project that encompasses more than five (5) acres of land, the Permitee shall be required to submit a Storm Water Pollution Protection Plan ("SWPPP").
 - B. The applicant's SWPPP shall be approved by the City Engineer prior to any on or off-site grading being done in relation to this project.
 - C. The applicant shall ensure that the required SWPPP is available for inspection at the project site at all times through and including acceptance of all improvements by the City.

- D. The applicant's SWPPP shall include provisions for all of the following Best Management Practices ("BMPs") (8.70.020 (Definitions), LQMC):
 - 1) Temporary Soil Stabilization (erosion control).
 - 2) Temporary Sediment Control.
 - 3) Wind Erosion Control.
 - 4) Tracking Control.
 - 5) Non-Storm Water Management.
 - 6) Waste Management and Materials Pollution Control.
- E. All of applicant's erosion and sediment control BMPs shall be approved by the City Engineer prior to any on or off site grading being done in relation to this project.
- F. All approved project BMPs shall be maintained in their proper working order throughout the course of construction, and until all improvements have been accepted by the City.
- 5. Permits issued under this approval shall be subject to the provisions of the Infrastructure Fee Program and Development Impact Fee program in effect at the time of issuance of building permit(s).

PROPERTY RIGHTS

- 6. Prior to issuance of any permit(s), the applicant shall acquire or confer easements and other property rights necessary for the construction or proper functioning of the proposed development. Conferred rights shall include irrevocable offers to dedicate or grant access easements to the City for emergency services and for maintenance, construction and reconstruction of essential improvements.
- 7. The applicant shall offer for dedication on the Parcel Map all public street right-of-ways in conformance with the City's General Plan, Municipal Code, applicable specific plans, and/or as required by the City Engineer.
- 8. The public street right-of-way offers for dedication required for this development include:

A. PUBLIC STREETS

- 1) Avenida Bermudas The applicant shall dedicate right of way to accommodate the existing bus stop turn out or modifications to the bus turn out as a result of the proposed development. The proposed right of way shall extend a minimum of 10 feet behind or even with the bus stop pad, which ever is greater.
- 9. The applicant shall retain for private use on the Parcel Map all private street right-of-ways in conformance with the City's General Plan, Municipal Code, applicable specific plans, and/or as required by the City Engineer.
- 10. Dedications shall include additional widths as necessary for dedicated right and left turn lanes, bus turnouts, and other features contained in the approved construction plans.
- 11. When the City Engineer determines that access rights to the proposed street right-of-ways shown on the approved Tentative Parcel Map are necessary prior to approval of the Parcel Map dedicating such right-of-ways, the applicant shall grant the necessary right-of-ways within 60 days of a written request by the City.
- 12. The applicant shall offer for dedication on the Parcel Map a ten-foot wide public utility easement contiguous with, and along both sides of all private streets. Such easement may be reduced to five feet in width with the express written approval of IID.
- 13. The applicant shall offer for dedication those easements necessary for the placement of, and access to, utility lines and structures, drainage basins, mailbox clusters, park lands, and common areas on the Parcel Map.
- 14. The applicant shall vacate all abutter's right-of-access to public streets and properties from all frontages along such public streets and properties, excepting those access points shown on the Parcel Map.
- 15. The applicant shall furnish proof of easements, or written permission, as appropriate, from those owners of all abutting properties on which grading, retaining wall construction, permanent slopes, or other encroachments will occur.

- 16. When an applicant proposes the vacation, or abandonment, of any existing right-of-way, or access easement, which will diminish the access rights to any properties owned by others, the applicant shall provide an alternate right-of-way or access easement, to those properties, or notarized letters of consent from the affected property owners.
- 17. The applicant shall cause no easement to be granted, or recorded, over any portion of the subject property between the date of approval of the Tentative Parcel Map and the date of recording of any Parcel Map, unless such easement is approved by the City Engineer.

PARCEL MAPS

18. Prior to the City's approval of a Parcel Map, the applicant shall furnish accurate AutoCAD files of the Parcel Map that was approved by the City's map checker on a storage media acceptable to the City Engineer. Such files shall be in a standard AutoCAD format so as to be fully retrievable into a basic AutoCAD program.

Where a Parcel Map was not produced in an AutoCAD format, or produced in a file that can be converted to an AutoCAD format, the City Engineer will accept a raster-image file of such Parcel Map.

IMPROVEMENT PLANS

As used throughout these Conditions of Approval, professional titles such as "engineer," "surveyor," and "architect," refer to persons currently certified or licensed to practice their respective professions in the State of California.

- 19. Improvement plans shall be prepared by or under the direct supervision of qualified engineers and/or architects, as appropriate, and shall comply with the provisions of Section 13.24.040 (Improvement Plans), LQMC.
- 20. The following improvement plans shall be prepared and submitted for review and approval by the City. A separate set of plans for each line item specified below shall be prepared. The plans shall utilize the minimum scale specified, unless otherwise authorized by the City Engineer in writing. Plans may be prepared at a larger scale if additional detail or plan clarity is desired. Note, the applicant

may be required to prepare other improvement plans not listed here pursuant to improvements required by other agencies and utility purveyors.

- A. Perimeter Landscape Plan: 1" = 20' Horizontal
- B. Site Development Plans: 1" = 30' Horizontal
- C. On-Site Utility Plan: 1" = 40' Horizontal
- D. On-Site Landscape Plan: 1" = 20' Horizontal

The plans shall be submitted a minimum of 8 to 10 weeks prior to the issuance of construction permits to allow adequate time for plan check and revisions.

Other engineered improvement plans prepared for City approval that are not listed above shall be prepared in formats approved by the City Engineer prior to commencing plan preparation.

"Site Development" plans shall normally include all on-site surface improvements including but not necessarily limited to finish grades for curbs & gutters, building floor elevations, parking lot improvements and ADA requirements; and show the existing street improvements out to at least the center lines of adjacent existing streets.

"Site Utility" plans shall normally include all sub-surface improvements including but not necessarily limited to sewer lines, water lines, fire protection and storm drainage systems.

21. The City maintains standard plans, detail sheets and/or construction notes for elements of construction. For a fee, established by City Resolution, the applicant may purchase such standard plans, detail sheets and/or construction notes from the City.

The applicant shall furnish a complete set of the AutoCAD files of all approved improvement plans on a storage media acceptable to the City Engineer. The files shall be saved in a standard AutoCAD format so they may be fully retrievable through a basic AutoCAD program.

At the completion of construction, and prior to the final acceptance of the improvements by the City, the applicant shall update the AutoCAD files in order to reflect the <u>as-built</u> conditions.

Where the improvement plans were not produced in a standard AutoCAD format, or a file format that can be converted to an AutoCAD format, the City Engineer will accept raster-image files of the plans.

IMPROVEMENT SECURITY AGREEMENTS

- 22. Prior to the conditional approval of any Parcel Map, or the issuance of any permit(s), the applicant shall construct all on and off-site improvements and satisfy its obligations for same, or shall furnish a fully secured and executed Subdivision Improvement Agreement ("SIA") guaranteeing the construction of such improvements and the satisfaction of its obligations for same, or shall agree to any combination thereof, as may be required by the City.
- 23. Any Subdivision Improvement Agreement ("SIA") entered into by and between the applicant and the City of La Quinta, for the purpose of guaranteeing the completion of any improvements related to this Tentative Parcel Map, shall comply with the provisions of Chapter 13.28 (Improvement Security), LQMC.
- 24. Improvements to be made, or agreed to be made, shall include the removal of any existing structures or other obstructions which are not a part of the proposed improvements; and shall provide for the setting of the final survey monumentation.
- 25. When improvements are phased through a "Phasing Plan," or an administrative approval (e.g., Site Development Permits), all off-site improvements and common on-site improvements (e.g., backbone utilities, storm drain improvements, perimeter walls, landscaping and gates) shall be constructed, or secured through a SIA, prior to the issuance of any permits in the first phase of the development, or as otherwise approved by the City Engineer.

Improvements and obligations required of each subsequent phase shall either be completed, or secured through a SIA, prior to the occupancy of permanent buildings within such latter phase, or as otherwise approved by the City Engineer.

In the event the applicant fails to construct the improvements for the development, or fails to satisfy its obligations for the development in a timely manner, pursuant to the approved phasing plan, the City shall have the right to halt issuance of all permits, and/or final inspections, withhold other approvals

related to the development of the project, or call upon the surety to complete the improvements.

26. When improvements are to be secured through a SIA, and prior to any conditional approval of the Parcel Map by the City Council, the applicant shall submit detailed construction cost estimates for all proposed on-site and off-site improvements, including an estimate for the final survey monumentation, for checking and approval by the City Engineer. Such estimates shall conform to the unit cost schedule adopted by City resolution, or ordinance.

For items not listed in the City's unit cost schedule, the proposed unit costs shall be approved by the City Engineer.

At the time the applicant submits its detailed construction cost estimates for conditional approval of the Parcel Map by the City Council, the applicant shall also submit one copy each of an 8-1/2" x 11" reduction of each page of the Parcel Map, along with a copy of an 8-1/2" x 11" Vicinity Map.

Estimates for improvements under the jurisdiction of other agencies shall be approved by those agencies and submitted to the City along with the applicant's detailed cost estimates.

Security will not be required for telephone, natural gas, or Cable T.V. improvements.

Development-wide improvements shall not be agendized for final acceptance by the City Council until the City receives confirmation from the telephone authority that the applicant has met all the requirements for telephone service to all lots within the development.

27. Should the applicant fail to construct the improvements for the development, or fail to satisfy its obligations for the development in a timely manner, the City shall have the right to halt issuance of building permits, and/or final building inspections, withhold other approvals related to the development of the project, or call upon the surety to complete the improvements.

GRADING

28. The applicant shall comply with the provisions of Section 13.24.050 (Grading Improvements), LQMC.

- 29. Prior to occupancy of the project site for any construction, or other purposes, the applicant shall obtain a grading permit approved by the City Engineer.
- 30. To obtain an approved grading permit, the applicant shall submit and obtain approval of all of the following:
 - A. A grading plan prepared by a qualified engineer or architect,
 - B. A preliminary geotechnical ("soils") report prepared by a qualified engineer, and
 - C. A Fugitive Dust Control Plan prepared in accordance with Chapter 6.16, (Fugitive Dust Control), LQMC.

All grading shall conform to the recommendations contained in the Preliminary Soils Report, and shall be certified as being adequate by a soils engineer, or by an engineering geologist.

A statement shall appear on the Parcel Map that a soils report has been prepared in accordance with the California Health & Safety Code § 17953.

The applicant shall furnish security, in a form acceptable to the City, and in an amount sufficient to guarantee compliance with the approved Fugitive Dust Control Plan provisions as submitted with its application for a grading permit.

- 31. The applicant shall maintain all open graded, undeveloped land in order to prevent wind and/or water erosion of such land. All open graded, undeveloped land shall either be planted with interim landscaping, or stabilized with such other erosion control measures, as were approved in the Fugitive Dust Control Plan.
- 32. Slopes shall not exceed 5:1 within public rights of way and 3:1 in landscape areas outside the right of way unless otherwise approved by the City Engineer.
- 33. Building pad elevations of perimeter lots shall not differ by more that one foot from the building pads in adjacent developments.
- 34. The applicant shall minimize the differences in elevation between the adjoining properties and the lots within this development.

Building pad elevations on contiguous interior lots shall not differ by more than three feet.

Where compliance within the above stated limits is impractical, the City may consider alternatives that are shown to minimize safety concerns, maintenance difficulties and neighboring-owner dissatisfaction with the grade differential.

- 35. Prior to any site grading or regrading that will raise or lower any portion of the site by more than plus or minus three tenths of a foot from the elevations shown on the approved Tentative Parcel Map or Site Development Permits, the applicant shall submit the proposed grading changes to the City Staff for a substantial conformance finding review.
- 36. Prior to the issuance of a building permit for any building lot, the applicant shall provide a lot pad certification stamped and signed by a qualified engineer or surveyor.

Each pad certification shall list the pad elevation as shown on the approved grading plan, the actual pad elevation and the difference between the two, if any. Such pad certification shall also list the relative compaction of the pad soil. The data shall be organized by lot number, and listed cumulatively if submitted at different times.

37. This development shall comply with Chapter 8.11 (Flood Hazard Regulations), LOMC. If any portion of any proposed building lot in the development is or may be located within a flood hazard area as identified on the City's Flood Insurance Rate Maps, the development shall be graded to ensure that all floors and exterior fill (at the foundation) are above the level of the project (100-year) flood and building pads are compacted to 95% Proctor Density as required in Title 44 of the Code of Federal Regulations, Section 65.5(a) (6). Prior to issuance of building permits for lots which are so located, the applicant shall furnish elevation certifications, as required by FEMA, that the above conditions have been met.

DRAINAGE

38. The applicant may discharge run off generated from the development to the existing storm drain system.

- 39. Nuisance water shall be retained on site in an acceptable manner.
- 40. The design of the development shall not cause any increase in flood boundaries, levels or frequencies in any area outside the development.
- 41. Storm drainage historically received from adjoining property shall be received and retained or passed through into the historic downstream drainage relief route.

UTILITIES

- 42. The applicant shall comply with the provisions of Section 13.24.110 (Utilities), LQMC.
- 43. The applicant shall obtain the approval of the City Engineer for the location of all utility lines within any right-of-way, and all above-ground utility structures including, but not limited to, traffic signal cabinets, electric vaults, water valves, and telephone stands, to ensure optimum placement for practical and aesthetic purposes.
- 44. Existing overhead utility lines within, or adjacent to the proposed development, and all proposed utilities shall be installed underground.
 - All existing utility lines attached to joint use 92 KV transmission power poles are exempt from the requirement to be placed underground.
- 45. Underground utilities shall be installed prior to overlying hardscape. For installation of utilities in existing improved streets, the applicant shall comply with trench restoration requirements maintained, or required by the City Engineer.

The applicant shall provide certified reports of all utility trench compaction for approval by the City Engineer.

PARKING LOT/STREET IMPROVEMENTS AND ACCESS POINTS

46. General access points and turning movements of traffic are limited to the following:

- A. Primary Entry: Mid Block on Calle Tampico Right turn in, Right turn out.
- B. Primary Entry: Mid Block on Avenida La Fonda Right turn in, Right turn out.
- C. Primary Entry(s): Two entries are allowed on Avenida Bermudas Full turning movements.
- D. Primary Entry(s): Two entries are allowed on Desert Club Drive Full turning movements.
- 47. Improvements shall include appurtenances such as traffic control signs, markings and other devices, raised medians if required, street name signs and sidewalks. Mid-block street lighting is not required.
- 48. Improvements shall be designed and constructed in accordance with City adopted standards, supplemental drawings and specifications, or as approved by the City Engineer. Improvement plans for streets, access gates and parking areas shall be stamped and signed by qualified engineers.
- 49. The applicant shall modify/relocate the Avenida Bermudas bus turn out as necessary to accommodate proposed driveway(s). The bus turn out modification is subject to approval by the City Engineer and SunLine.

CONSTRUCTION

- 50. The applicant shall submit current mix designs (less than two years old at the time of construction) for base, asphaltic concrete and Portland cement concrete. The submittal shall include the test results for all specimens used in the mix design procedure. For mix designs over six months old, the submittal shall include the most recent (less than six months old at the time of construction) aggregate gradation test results confirming that the design gradations can be achieved in current production. The applicant shall not schedule construction operations until mix designs have been approved.
- 51. The City will conduct final inspections of habitable buildings only when the buildings have improved street and (if required) sidewalk access to publicly-maintained streets. The improvements shall include required traffic control devices, pavement markings and street name signs. If on-site streets in residential developments are initially constructed with partial pavement thickness, the applicant shall complete the pavement prior to final inspections

of the last ten percent of homes within the development or when directed by the City, whichever comes first.

LANDSCAPING

- 52. The applicant shall comply with Sections 13.24.130 (Landscaping Setbacks) & 13.24.140 (Landscaping Plans), LQMC.
- 53. The applicant shall provide landscaping in the required setbacks, retention basins, common lots and park areas.
- 54. Landscape and irrigation plans for landscaped lots and setbacks, medians, retention basins, and parks shall be signed and stamped by a licensed landscape architect.

The applicant shall submit the landscape plans for approval by the Community Development Department (CDD), prior to plan checking by the Public Works Department. When plan checking has been completed by CDD, the applicant shall obtain the signatures of CVWD and the Riverside County Agricultural Commissioner, prior to submittal for signature by the City Engineer.

NOTE: Plans are not approved for construction until signed by the City Engineer.

55. Landscape areas shall have permanent irrigation improvements meeting the requirements of the City Engineer. Use of lawn areas shall be minimized with no lawn, or spray irrigation, being placed within 18 inches of curbs along public streets.

PUBLIC SERVICES

56. The applicant shall provide public transit improvements as required by SunLine Transit Agency and approved by the City Engineer.

QUALITY ASSURANCE

- 57. The applicant shall employ construction quality-assurance measures that meet with the approval of the City Engineer.
- 58. The applicant shall employ, or retain, qualified engineers, surveyors, and such other appropriate professionals as are required to provide the expertise with

which to prepare and sign accurate record drawings, and to provide adequate construction supervision.

- 59. The applicant shall arrange for, and bear the cost of, all measurements, sampling and testing procedures not included in the City's inspection program, but which may be required by the City, as evidence that the construction materials and methods employed comply with the plans, specifications and other applicable regulations.
- 60. Upon completion of construction, the applicant shall furnish the City with reproducible record drawings of all improvement plans which were approved by the City. Each sheet shall be clearly marked "Record Drawing," "As-Built" or "As-Constructed" and shall be stamped and signed by the engineer or surveyor certifying to the accuracy and completeness of the drawings. The applicant shall have all AutoCAD or raster-image files previously submitted to the City, revised to reflect the as-built conditions.

MAINTENANCE

- 61. The applicant shall comply with the provisions of Section 13.24.160 (Maintenance), LQMC.
- 62. The applicant shall make provisions for the continuous and perpetual maintenance of all private on-site improvements, perimeter landscaping, access drives, and sidewalks.

FEES AND DEPOSITS

63. The applicant shall comply with the provisions of Section 13.24.180 (Fees and Deposits), LQMC. These fees include all deposits and fees required by the City for plan checking and construction inspection. Deposits and fee amounts shall be those in effect when the applicant makes application for plan check and permits.

FIRE DEPARTMENT

64. The water mains shall be capable of providing a potential fire flow of 2500 gpm and the actual fire flow available from any one fire hydrant connected to any given water main shall be 1500 gpm for a 2-hour duration at 20-psi residual operating pressure.

- 65. Approved fire hydrants shall be located at each street intersection, if possible, but in no events shall there be an interval of more than 330 feet between hydrants.
- 66. Blue dot reflectors shall be placed in the street 8 inches from the centerline to the side that the fire hydrant is on, to identify fire hydrant locations.
- 67. Each commercial building shall be equipped with a KNOX key box system for rapid entry.
- 68. Water plans shall be submitted to the Fire Department for review prior to recordation.
- 69. The required water system, including fire hydrants, shall be installed and accepted by the appropriate water agency prior to any combustible building material being placed on an individual lot.